



Waved neck bar

With the waved neck bar the shoulder height or diagonal boxside - neck rail can be raised up till 30 cm.

Mainly applied with dividers of 190 cm in, for example renovations. The waved neck bar has on one side reduced end part which is used to connect two dividers.

Major characteristics:

- The waved neck bar makes a large adjustment of the diagonal possible;
- The place of the shoulder rail clamp can be put back steady;
- A guiding effect. It forces the cow to stay straight;
- Available for divider width 110, 112.5, 115, 120 and 125 cm;
- In between measurements can be realized through combining different dimensions of waved neck bar. For example: a divider width of 117.5 cm, place 2 x 115 cm and 2 x 120 cm;
- Connected per 2 divider places;

	item no.
Waved neck bar 2 x 110 cm	01.91.110
Waved neck bar 2 x 112.5 cm	01.91.112
Waved neck bar 2 x 115 cm	01.91.115
Waved neck bar 2 x 120 cm	01.91.120
Waved neck bar 2 x 125 cm	01.91.125

Starting wave neck bar - 50 cm	01.91.150
--------------------------------	------------------

Fittings wall fastening

End coupling 48 mm	04.24.015
Floor anchor M10 x 71 mm (2 per end coupling)	11.11.210
Bolt M10 x 60	71.10.060
Nut M10	82.10.100

